Spectrum
Division of United Industries Corp.
P.O. Box 15842
St. Louis, MO 63114

Material Safety Data Sheet

Complies with OSHA's Hazard Communication Standard, 29 CFR 1910.1200

Hazardous Material Identification System-(HMIS)

HEALTH - 2

REACTIVITY - 0

FLAMMABILITY - 3

PERSONAL - None

Droduct Type: In	east Panallant Associal				
	sect Repellent Aerosol				
EPA Registration Number		Manufacturer		Emergency Telephone No.	
121-33		Chemsico 8494 Chapin Industrial Drive St. Louis, MO 63114		For Chemical Emergency: For Information: Prepared by: Date Prepared:	1-800-633-287 1-800-332-555 H.L. Paul May 10, 199
II Hazardous Ingredients/Identity Information			III Physical and Chemical Characteristics		
Chemical N,N-diethyl-m- Toluamide (DEET) CAS #134-62-3 SDA-40 Ethanol CAS 64-17-5 Isobutane CAS #75-28-5	% OSHA PEL 23 NA 54 NA 20 NE	ACGIH TLV NA 1000 ppm NE	Appearance and (Boiling Point: Vapor Pressure: Specific Gravity: Vapor Density: % Volatile (by vo Solubility in Wate Evaporation Rate	er: Not known	liquid with ethanol
IV Fire and Explosion Hazard Data			V Reactivity Data		
Flash Point: Flame Extension: Flammable Limits: Autoignition Temp.: Fire Extinguishing Me Decomposition Temp.: Special Fire-Fighting F	Lower: 3 793°F dia: CO ₂ , Foat N/A Procedures: For smal dry chem For large amounts of	el 2 Aerosol) .3% Upper: 19.0% m, Dry Chemical l fires: Use CO ₂ , or ical extinguishers. e fires: Use copious of water.	Stability: Polymerization: Conditions to Avo Incompatible Mat Hazardous Decon or Byproducts	terials: May soften or day such as rayon. Ma apposition	nage some synthetic ay damage leather.
VI Health Hazard Data			VII Precautions for Safe Handling and Use		
Ingestion (Swallowing): Harmful if swallowed. First Aid: Consult a physician or poison control. If conscious, give one or two glasses of water and induce vorniting. Do not induce vorniting or give anything by mouth to an unconscious person. Eye Contact: May cause eye injury. First Aid: Flush eyes with plenty of water for 15. Get medical attention. If skin reaction occurs, wash with soap and water. Get medical attention if irritation persists. Vapors may cause respiratory irritation. First Aid: Remove to fresh air. Special Notes: Apply only to skin or clothing, do not ingest. Keep out of eyes. Frequent reapplication or saturation is unnecessary Health Conditions Aggravated by Exposure: None Known Ingredients listed by NTP, OSHA or IARC as Carcinogens or potential carcinogens: None			Steps to be Taken in Case Material is Released or Spilled: Flammable material. Remove all possible ignition sources. Wipe up with absorbent material. Wash small quantities away with soapy water. Prevent bulk quantities from entering open sewers and waterways. Waste Disposal: This material is flammable and must be disposed of in accordance with Local, State, and Federal regulations. Do not reuse empty container; dispose of properly. Handling & Storage Precautions: Keep away from heat, sparks, or open flame. Do not expose treated skin to fire, sparks or flam until liquid has dried.		
VIII Control Measures			IX Transportation Data		
Read and follow label directions. They are your best guide to using this product effectively, and give necessary safety precautions to protect your health.			DOT Shipping Name - Consumer Commodity DOT Hazard Class - ORM-D		

The information and statements herein are believed to be reliable but are not to be construed as warranty or representation for which we assume legal responsibility. Users should undertake sufficient verification and testing to determine the suitability for their own particular purpose of any information or products referred to herein. NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE IS MADE.